

High-performance winch TW 9500

Technical Data

6.8 PS / 12 VDC Motor: Pulling Power: 4.950 kg

Solenoid: waterproof IP 68

Tri-metal Drum bearing:

Scope of delivery: 30 m synthetic rope, HD-hook, aluminum fairlead, remote control

Line speed: 18m/min

Features:

Alloy housing, motor and drum additionally sealed. Reinforced brake and HD-planetary set. Forged gear set, hardened and polished for precision and durability even under toughest conditions



TIBUS Offroad Ltd. & Co. KG

Roffhausener Landstrasse 25 26419 Schortens / Germany Tel.: +49 (0) 4421 70 69 1 Fax: +49 (0) 4421 70 19 10 info@tibus-offroad.com www.tibus-offroad.com



Are you interested?

We want you to be completely satisfied. With us you will not get any products "off the shelf". To equip your vehicle with high-grade TIBUS winch is rather complex and we want to advice and discuss to find out what ever is the best solution for your needs.

Let us know your expectations and we will provide you with a detailed offer which is perfectly adapted to your requirements. We look forward to your project.



You may scan the QR-code and contact us or simply call us:

+49 (0) 4421 70 69 1



The remote control of the TW 9500 is detachable and waterproof. With the 3 meter cable length a safe operation of the winch is assured even in difficult situations.



The TW-9500 is powered with a 6.8 HP serious wound motor and provides up to 4.6 t pulling power and 18 m/min line speed. The HD planetary set ensures maximum stability even under toughest conditions. The relay is waterproof, the brake reinforced.



The TIBUS TW-9500 low profile winch is designed for a 12-volt electrical system. It's shipped complete with 30m synthetic rope, HD-hook, aluminum fairlead, remote control, sealed (IP68) housing and solenoid.